

## ALUMINUM ELECTROLYTIC CAPACITORS

- Load life 2000 hours at 105°C
- High ripple current

### ■ SPECIFICATIONS

Item	Characteristics																
Operating Temperature Range(°C)	-40~+105(>160V, -25~+105)																
Rated Voltage Range (V)	16~450																
Nominal capacitance range (μF)	39~47000																
Capacitance Tolerance(20°C,120Hz)	±20%																
Leakage current (μA)	I≤0.01CV or 1.5mA whichever is smaller (at 20°C, after 5 minutes) C: Nominal Capacitance (μF) V: Rated Voltage (V)																
Dissipation Factor(20°C,120Hz)	<table border="1"> <thead> <tr> <th>Rated voltage (v)</th> <th>16</th> <th>25</th> <th>35</th> <th>50</th> <th>63~100</th> <th>160~400</th> <th>450</th> </tr> </thead> <tbody> <tr> <td>tanδ</td> <td>0.50</td> <td>0.40</td> <td>0.35</td> <td>0.30</td> <td>0.20</td> <td>0.15</td> <td>0.20</td> </tr> </tbody> </table>	Rated voltage (v)	16	25	35	50	63~100	160~400	450	tanδ	0.50	0.40	0.35	0.30	0.20	0.15	0.20
Rated voltage (v)	16	25	35	50	63~100	160~400	450										
tanδ	0.50	0.40	0.35	0.30	0.20	0.15	0.20										
Temperature Stability(120Hz)	<table border="1"> <thead> <tr> <th colspan="2">Rated voltage (v)</th> <th>16~100</th> <th>160~200</th> <th>250~450</th> </tr> </thead> <tbody> <tr> <td rowspan="2">Impedance Ratio</td> <td>Z-25°C/Z+20°C</td> <td>4</td> <td>4</td> <td>4</td> </tr> <tr> <td>Z-40°C/Z+20°C</td> <td>15</td> <td>-</td> <td>-</td> </tr> </tbody> </table>	Rated voltage (v)		16~100	160~200	250~450	Impedance Ratio	Z-25°C/Z+20°C	4	4	4	Z-40°C/Z+20°C	15	-	-		
Rated voltage (v)		16~100	160~200	250~450													
Impedance Ratio	Z-25°C/Z+20°C	4	4	4													
	Z-40°C/Z+20°C	15	-	-													
Load Life(+105°C)	<table border="1"> <tbody> <tr> <td>Time</td> <td>2000 hours</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ±20% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 200% of the specified value.</td> </tr> </tbody> </table>	Time	2000 hours	Leakage Current	Not more than the specified value.	Capacitance Change	Within ±20% of the initial value.	Dissipation Factor	Not more than 200% of the specified value.								
Time	2000 hours																
Leakage Current	Not more than the specified value.																
Capacitance Change	Within ±20% of the initial value.																
Dissipation Factor	Not more than 200% of the specified value.																
Shelf Life(+105°C)	<table border="1"> <tbody> <tr> <td>Time</td> <td>500 hours</td> </tr> <tr> <td>Leakage Current</td> <td>Not more than the specified value.</td> </tr> <tr> <td>Capacitance Change</td> <td>Within ±20% of the initial value.</td> </tr> <tr> <td>Dissipation Factor</td> <td>Not more than 200% of the specified value.</td> </tr> </tbody> </table> <p>After test: Rated voltage to be applied for 30 minutes, 24 to 48 hours before measurement.</p>	Time	500 hours	Leakage Current	Not more than the specified value.	Capacitance Change	Within ±20% of the initial value.	Dissipation Factor	Not more than 200% of the specified value.								
Time	500 hours																
Leakage Current	Not more than the specified value.																
Capacitance Change	Within ±20% of the initial value.																
Dissipation Factor	Not more than 200% of the specified value.																

### ■ DIMENSIONS

MM

### ■ MULTIPLIER FOR RIPPLE CURRENT

	<b>Frequency coefficient</b>																													
	<table border="1"> <thead> <tr> <th>Freq (Hz)</th> <th>50</th> <th>120</th> <th>1K</th> <th>10K</th> <th>20K</th> </tr> </thead> <tbody> <tr> <td>Rated Voltage(V) ≤100</td> <td>0.95</td> <td>1</td> <td>1.10</td> <td>1.15</td> <td>1.15</td> </tr> <tr> <td>160~250</td> <td>0.87</td> <td>1</td> <td>1.11</td> <td>1.18</td> <td>1.2</td> </tr> <tr> <td>≥315</td> <td>0.80</td> <td>1</td> <td>1.14</td> <td>1.14</td> <td>1.2</td> </tr> </tbody> </table>	Freq (Hz)	50	120	1K	10K	20K	Rated Voltage(V) ≤100	0.95	1	1.10	1.15	1.15	160~250	0.87	1	1.11	1.18	1.2	≥315	0.80	1	1.14	1.14	1.2					
	Freq (Hz)	50	120	1K	10K	20K																								
	Rated Voltage(V) ≤100	0.95	1	1.10	1.15	1.15																								
160~250	0.87	1	1.11	1.18	1.2																									
≥315	0.80	1	1.14	1.14	1.2																									
<b>Temperature coefficient</b>																														
<table border="1"> <thead> <tr> <th>Temperature(°C)</th> <th>+40</th> <th>+55</th> <th>+70</th> <th>+80</th> <th>+105</th> </tr> </thead> <tbody> <tr> <td>Coefficient</td> <td>2.7</td> <td>2.5</td> <td>2.1</td> <td>1.7</td> <td>1</td> </tr> </tbody> </table>	Temperature(°C)	+40	+55	+70	+80	+105	Coefficient	2.7	2.5	2.1	1.7	1																		
Temperature(°C)	+40	+55	+70	+80	+105																									
Coefficient	2.7	2.5	2.1	1.7	1																									

## ■ STANDARD RATINGS

WV(V)	16		25		35		50		63		80		100	
	Cap μF	Ripple (A)	Cap μF	Ripple (A)	Cap μF	Ripple (A)	Cap μF	Ripple (A)	Cap μF	Ripple (A)	Cap μF	Ripple (A)	Cap μF	Ripple (A)
22X25	4700	1.4	3300	1.3	2200	1.1	1200	0.96	820	0.92	560	0.76	390	0.64
22x25	6800	1.60	4700	1.55	3300	1.43	1800	1.31	1200	1.25	820	1.11	560	1.07
22x30	10000	1.99	6800	1.91	3900	1.65	2700	1.70	1800	1.52	1200	1.39	820	1.35
22x35	12000	2.28	8200	2.14	5600	2.02	3300	1.98	2200	1.73	1500	1.61	1000	1.54
22x40	15000	2.64	10000	2.40	6800	2.28	3900	2.25	2700	1.97	1800	1.83	1200	1.74
22x45	18000	2.98	12000	2.69	--	--	4700	2.56	--	--	2200	2.09	1500	1.99
22x50	--	--	--	--	8200	2.67	5600	2.89	3300	2.32	--	--	--	--
25x25	10000	1.99	6800	1.91	4700	1.78	2700	1.70	1800	1.52	1200	1.39	820	1.35
25x30	12000	2.30	8200	2.16	5600	2.04	3300	2.00	2200	1.75	1500	1.62	1000	1.56
25x35	15000	2.68	10000	2.44	6800	2.31	3900	2.28	2700	1.99	2200	2.01	1200	1.76
25x40	18000	3.04	12000	2.74	8200	2.60	5600	2.81	3300	2.27	--	--	1500	2.03
25x45	22000	3.40	15000	3.15	10000	2.92	--	--	3900	2.54	2700	2.43	1800	2.28
25x50	27000	3.81	18000	3.54	12000	3.26	6800	3.37	4700	2.88	3300	2.76	2200	2.57
30x25	12000	2.38	8200	2.25	5600	2.12	3900	2.22	2700	1.93	1800	1.81	1200	1.71
30x30	18000	3.00	12000	2.70	8200	2.56	4700	2.58	300	2.24	2200	2.10	1500	2.00
30x35	22000	3.39	15000	3.13	10000	2.92	5600	2.95	3900	2.55	2700	2.43	1800	2.27
30x40	27000	3.83	18000	3.54	12000	3.28	6800	3.39	4700	2.90	3300	2.78	2200	2.59
30x45	33000	4.30	22000	4.24	15000	3.74	8200	3.71	5600	3.28	3900	3.12	2700	2.94
30x50	39000	4.74	--	--	--	--	10000	4.09	6800	3.73	4700	3.56	3300	3.32
35x25	18000	3.10	12000	2.80	8200	2.78	4700	2.67	3300	2.41	2200	2.17	1500	2.07
35x30	27000	3.74	15000	3.22	12000	3.20	6800	3.31	4700	2.83	3300	2.71	2200	2.52
35x35	33000	4.24	22000	3.96	15000	3.69	8200	3.66	5600	3.24	3900	3.07	2700	2.90
35x40	39000	4.72	--	--	18000	4.16	10000	4.07	6800	3.71	4700	3.50	3300	3.31
35x45	47000	5.27	27000	4.75	--	--	12000	4.50	8200	4.16	5600	3.87	3900	3.69
35x50	--	--	33000	5.39	22000	4.92	--	--	10000	4.69	6800	4.19	4700	4.14

WV(V)	160		180		200		250		350		400		450	
	Cap μF	Ripple (A)	Cap μF	Ripple (A)	Cap μF	Ripple (A)	Cap μF	Ripple (A)	Cap μF	Ripple (A)	Cap μF	Ripple (A)	Cap μF	Ripple (A)
22X25	180	0.65	220	0.65	150	0.60	100	0.45	56	0.37	39	0.32		
22x25	330	1.16	270	1.08	220	1.08	180	0.94	68	0.56	68	0.47	56	0.47
22x30	390	1.43	330	1.30	330	1.30	220	1.10	100	0.70	82	0.56	68	0.56
22x35	470	1.52	470	1.50	390	1.41	270	1.13	120	0.73	120	0.64	82	0.64
22x40	560	1.62	560	1.62	470	1.50	330	1.20	150	0.79	150	0.70	100	0.70
22x45	680	1.70	--	--	560	1.58	390	1.26	180	0.81	--	--	120	0.73
22x50	820	1.81	680	1.76	680	1.68	470	1.37	220	0.93	180	0.78	150	0.78
25x25	470	1.55	390	1.35	330	1.35	220	1.15	100	0.70	82	0.65	68	0.65
25x30	560	1.73	470	1.62	470	1.47	330	1.30	150	0.82	120	0.70	100	0.70
25x35	680	1.81	560	1.69	560	1.65	390	1.41	180	0.89	150	0.73	120	0.73
25x40	820	1.98	680	1.72	680	1.80	470	1.52	220	0.97	180	0.82	150	0.82
25x45	1000	2.04	820	1.78	--	--	560	1.59	--	--	220	0.87	180	0.87
25x50	1200	2.12	1000	1.91	820	1.87	680	1.66	270	1.01	270	0.94	220	0.94
30x25	680	1.82	560	1.67	470	1.56	330	1.30	150	0.82	120	0.78	100	0.78
30x30	820	1.98	680	1.74	680	1.82	470	1.36	180	0.90	180	0.83	150	0.83
30x35	1000	2.14	820	1.85	820	1.99	560	1.57	270	1.05	220	0.86	180	0.86
30x40	1200	2.22	1000	2.01	--	--	680	1.76	--	--	270	0.95	220	0.95
30x45	1500	2.46	1200	2.19	1000	2.17	820	1.83	330	1.16	330	1.11	270	1.11
30x50	--	--	1500	2.36	1200	2.22	1000	1.87	390	1.26	390	1.15	330	1.15
35x25	820	1.93	680	1.92	680	1.96	470	1.40	220	0.98	180	0.86	150	0.86
35x30	1200	2.40	1000	2.16	820	2.07	560	1.56	270	1.01	270	0.91	220	0.91
35x35	1500	2.53	1200	2.34	1000	2.22	820	1.82	330	1.16	330	1.13	270	1.13
35x40	--	--	1500	2.56	1200	2.42	1000	1.99	390	1.26	390	1.26	330	1.26
35x45	1800	2.98	1800	2.67	1500	2.59	1200	2.10	470	1.35	470	1.31	390	1.31
35x50	2200	3.10	--	--	1800	2.70	--	--	560	1.51	560	1.50	470	1.50

■ Ripple current: 105°C, 100Hz or 120Hz.

The specific capacitance and case size are available on request.